

Specifications

Synthetic Blend Engine Oil 5W30, Gibraltar Powerflo Synthetic Blend or Equal

This specification is to be used as a guide, rather than a restriction to the product being offered. The Town reserves the right to accept any bid which conforms to industry standards.

Specially formulated using synthetic and Group II base oils and high performance additive packages to provide superior performance in gasoline fueled and flex-fueled engines. These oils are formulated for excellent oxidation stability and low temperature properties to insure protection during cold starts. Meets or exceeds the requirements of ILSAC GF-5 and is "resource conserving" for improved fuel economy.

Properties

Density	7.17
Viscosity, cSt @ 100 C	10.8
Viscosity, CCS cP @-30 C	6000
Viscosity, cSt @ 40 C	67.0
Viscosity Index	160
Pour Point, C	-41
Zinc, Wt. (%)	0.085
Phosphorous, Wt. (%)	0.077
HT/HS cP @ 150 C	3.0
NOACK, Wt. (%)	14.5
API Service	SN
ILSAC GF-5	X

ALL FREIGHT CHARGES ARE TO BE INCLUDED. ANY BIDDER CHARGING FREIGHT WILL BE DISQUALIFIED.

NO MINIMUM REQUIREMENTS FOR DELIVERY. ANY BIDDER SETTING MINIMUMS MAY BE DISQUALIFIED.

The Town may award this bid in whole or in parts, or make no award at all, whichever is in the best interest of the Town.

All signatures are to be original. Do not remove any pages from the bid contract. Return the bid contract in its entirety.